

Model	Kapasite / Capacity					Isı Transfer Yüzeği Heat Exchanger Surface	Fan					Isıtıcılar Electrical Defrost		
	SC1	+2/-8	SC2	SC3	SC4		Cap Diameter	Hava Debisi Air Flow	Hava Atrm Mesafesi Air Throw	Elektrik Gücü Power Consumption	Ses Seviyesi Noise Level	HT	LT	
	Tr= 10°C Te= 0°C ΔT= 10K	Tr= +2°C Te= -8°C ΔT= 10K	Tr= 0°C Te= -8°C ΔT= 8K	Tr= -18°C Te= -25°C ΔT= 7K	Tr= -25°C Te= -31°C ΔT= 6K		m ²	mm	m ³ /h	m	Watt	dB(A)	Watt	Watt
SBL-61-125	1100	1000	750	510	410	2.7	1xØ250	810	5	95	43	1 x 300	2 x 300	1 x 300
SBL-62-125	1340	1210	900	700	560	3.6	1xØ250	760	5	95	43	2 x 300	2 x 300	1 x 300
SBL-64-125	1640	1500	1120	900	700	5.4	1xØ250	660	4	95	44	2 x 300	3 x 300	1 x 300
SBL-61-130	1830	1660	1240	1010	810	4.3	1xØ300	1450	8	66	48	1 x 400	2 x 400	1 x 400
SBL-62-130	2310	2090	1570	1220	990	5.8	1xØ300	1380	7	69	48	2 x 400	3 x 400	1 x 400
SBL-63-130	2680	2420	1810	1450	1170	7.2	1xØ300	1320	7	70	48	2 x 400	3 x 400	1 x 400
SBL-64-130	2940	2690	2010	1590	1290	8.7	1xØ300	1270	7	71	49	2 x 400	3 x 400	1 x 400
SBL-61-135	3330	2980	2230	1740	1330	7.0	1xØ350	2770	12	153	55	2 x 520	3 x 520	1 x 520
SBL-62-135	4130	3720	2780	2190	1760	9.4	1xØ350	2640	12	155	55	2 x 520	3 x 520	1 x 520
SBL-63-135	4720	4270	3190	2530	2050	11.7	1xØ350	2510	11	158	54	2 x 520	3 x 520	1 x 520
SBL-64-135	5280	4780	3570	2860	2280	14.1	1xØ350	2400	11	159	54	3 x 520	4 x 520	1 x 520
SBL-61-225	2170	1920	1440	1170	940	5.4	2xØ250	1620	6	190	46	1 x 600	2 x 600	1 x 600
SBL-62-225	2720	2460	1840	1430	1150	7.2	2xØ250	1520	6	190	46	2 x 600	2 x 600	1 x 600
SBL-64-225	3340	3050	2280	1800	1450	10.8	2xØ250	1320	5	190	47	2 x 600	3 x 600	1 x 600
SBL-61-230	3790	3420	2560	1960	1580	8.7	2xØ300	2890	9	132	51	1 x 800	2 x 800	1 x 800
SBL-62-230	4690	4220	3150	2390	1920	11.6	2xØ300	2760	8	138	51	2 x 800	3 x 800	1 x 800
SBL-63-230	5320	4870	3650	2920	2380	14.4	2xØ300	2640	8	140	51	2 x 800	3 x 800	1 x 800
SBL-64-230	5970	5420	4050	3260	2630	17.3	2xØ300	2530	8	142	52	3 x 800	4 x 800	1 x 800
SBL-61-235	6550	5950	4450	3510	2850	14.0	2xØ350	5540	13	306	58	2 x 1040	3 x 1040	1 x 1040
SBL-62-235	8360	7510	5620	4410	3550	18.8	2xØ350	5280	13	310	58	2 x 1040	3 x 1040	1 x 1040
SBL-63-235	9560	8610	6440	5160	4190	23.4	2xØ350	5020	12	316	57	3 x 1040	4 x 1040	1 x 1040
SBL-64-235	10560	9690	7250	5770	4730	28.2	2xØ350	4800	12	318	57	3 x 1040	4 x 1040	1 x 1040
SBL-61-325	3340	3030	2260	1810	1370	8.1	3xØ250	2430	7	285	48	1 x 900	2 x 900	1 x 900
SBL-62-325	4000	3670	2750	2220	1780	10.8	3xØ250	2280	7	285	48	2 x 900	2 x 900	1 x 900
SBL-64-325	5000	4570	3420	2770	2240	16.2	3xØ250	1980	6	285	49	2 x 900	3 x 900	1 x 900
SBL-61-330	5720	5000	3740	3070	2500	13.0	3xØ300	4340	10	198	53	2 x 1200	3 x 1200	1 x 1200
SBL-62-330	7040	6350	4750	3800	3070	17.3	3xØ300	4140	9	207	53	2 x 1200	3 x 1200	1 x 1200
SBL-63-330	8120	7370	5510	4330	3500	21.7	3xØ300	3960	9	210	53	2 x 1200	3 x 1200	1 x 1200
SBL-64-330	9000	8140	6090	4920	4000	26.0	3xØ300	3800	9	213	54	3 x 1200	4 x 1200	1 x 1200
SBL-61-335	9930	8940	6690	5210	4270	21.0	3xØ350	8310	14	459	60	2 x 1560	3 x 1560	1 x 1560
SBL-62-335	12400	11110	8310	6730	5350	28.0	3xØ350	7930	14	465	60	2 x 1560	3 x 1560	1 x 1560
SBL-63-335	14400	12980	9710	7760	6250	35.1	3xØ350	7540	13	474	59	3 x 1560	4 x 1560	1 x 1560
SBL-64-335	16040	14510	10850	8740	7100	42.1	3xØ350	7190	13	477	59	3 x 1560	4 x 1560	1 x 1560

ÜRÜN SEÇİMİ
PRODUCT SELECTIONKAPASİTE TABLOSU
CAPACITY TABLESÖLÇÜLER
MEASURESTEKNİK ÇİZİMLER
TECHNICAL DRAWINGSGENEL ÖZELLİKLER
SPECIFICATIONS